


Flanged DIN PN10/16 Double Window Sight Glass



- ASTM A351 CF8M 316 Stainless Steel construction.
- PTFE Glass Seals. Borosilicate Glass. Swinging Flap to indicate Flow.
- Bolted Glass Covers. DIN 3202 F-1 Face to Face dimension
- -20 / + 200 Deg C temperature rated. 10 Bar/g pressure rated.

A versatile, cost effective solution where visual flow indication is required within the pipeline construction.

Item	Part	Material	Qty.
1	Body	CF8M	1
2	Cap	CF8M	1
3	Gasket	PTFE	1
4	Stem	SUS316	1
5	Glass	BOROSILICATE	1
6	Indicator	CF8M	1
7	Bolt	SUS304	1

3.1 Material Certificates available.

Test standard – API 598

Available size range: 1/2" - 6"

SIZE	d	d1	L	H	D	C	G	f	T	N-øM
1/2"	15	35	130	115	95	65	45	2	14	4-ø14
3/4"	20	35	150	115	105	75	58	2	16	4-ø14
1"	25	35	160	115	115	85	68	2	16	4-ø14
1-1/4"	32	55	180	143	140	100	78	2	16	4-ø18
1-1/2"	40	55	200	143	150	110	88	3	16	4-ø18
2"	50	55	230	143	165	125	102	3	18	4-ø18
2-1/2"	65	85	290	185	185	145	122	3	18	4-ø18
3"	80	85	310	196	200	160	138	3	20	8-ø18
4"	100	110	350	228	220	280	158	3	20	8-ø18
6"	150	160	480	310	285	240	212	3	22	8-ø22

Pressure-Temp. Rating

