



Nominal Diameter	d	∅1	∅2	D	L	b	n-∅d1	Ra	Rb	A	B	KKK	H	V	
15	1/2"	15	35	60.5	89	108	10.5	4-∅16	3	3	36	42	9X9	80	140
20	3/4"	20	43	70	98	117	10.5	4-∅16	3	3	36	42	9X9	85	140
25	1"	25	51	79.5	108	127	10.5	4-∅16	3	3.5	42	50	11X11	93	165
32	1 1/4"	32	64	89	115	140	11.2	4-∅16	3	3.5	42	50	11X11	104	165
40	1 1/2"	38	73	98.5	125	165	12.7	4-∅16	3.5	4.5	50	70	14X14	115	195
50	2"	50	92	120.5	150	178	14.3	4-∅19	3.5	4.5	50	70	14X14	125	195
65	2 1/2"	64	105	139.5	178	190	15.9	4-∅19	4.5	5.5	70	102	17X17	145	260
80	3"	76	127	152.5	190	203	17.5	4-∅19	4.5	5.5	70	102	17X17	152	260
100	4"	96	157	190.5	229	229	22.3	8-∅19	4.5	5.5	70	102	17X17	180	300
125	5"	125	186	216	254	356	22.3	8-∅22	5.5	6.5	102	125	22X22	210	600
150	6"	150	216	241.5	279	394	23.9	8-∅22	5.5	6.5	102	125	27X27	225	600

- Features:
1. Pressure Rating: 150LBS
  2. Pull Port
  3. Working Temperature: -10° C-150° C
  4. Investment Casting
  5. Blow-out Proof Stem
  6. ISO5211 Mounting Pad
  7. Locking Device Handle (Option)
  8. Flange Dimension: ANSI B16.5 Class 150
  9. Face To Face: ANSI B16.10
  10. Inspection Testing: AP1598, EN12266-1

1	BODY	CF8M/CF8	1
2	SBAT	PTFE/RPTFE	2
3	BALL	316/304	1
4	GASKET	PTFE	1
5	BONNET	CF8M/CF8	1
6	BOLT	304	4-8
7	NUT	304	4-8
8	STEM	316/304	1
9	STEM WASHER	PTFE	1
10	O RING	NBR/PPM/BTDM	1
11	PACKING	PTFE	1
12	GLAND	304	1
13	DISC SPRING	304	2
14	NUT	304	2
15	CROWN WASHER	304	1
16	WASHER	304	1
17	HANDLE	304	1
18	HEX SOCKET BOLT	304	1
19	NUT	304	1
20	HANDLE COVER	PLASTIC	1
21	BOLT WASHER	304	4-8
NO.	PARTS	MATERIALS	QTY

DESC 2PC ANSI Flanged Ball Valve (ETG F-2/150)  
 G.C. SUPPLIES UK LIMITED