



FEATURES

- * The Screwed ends conform to ASME B1.20.1(NPT) DIN 2999 & BS21 ISO 228/1 & BS 21
- * Investment casting ASTM-A351
- * 600 PSI WORKING PRESSURE
- * Inside screw and Screwed bonnet Wedge disc.
- * Nonrising stem, and Handwheel.
- * Thread end: BSPT, BSP, NPT, DIN259
- * Integral seat, Beveled disc, wedge
- * 100% tested air-under water at 100 PSI

NO.	NAME OF PARTS	MATERIAL	Q'TY
1	BODY	304; 316; CF8M	1
2	DISC	304; 316; CF8M	1
3	STEM	304; 316	1
4	CAP	304; 316; CF8M	1
5	GASKET	PTFE	1
6	PACKING	PTFE	1set
7	CAP UNT	304; 316; CF8M	1
8	GLAND WASHER	304	1
9	SPIN WASHER	AISI 304	1
10	NUT	AISI 304	1
11	HANDLE	DUCT IRON	1

SIZE VALVE	1/2	3/4	1	1-1/4	1-1/2	2
L M/M	63	70	77	87	100	110
H M/M	106	106	116	122	144	145
D M/M	62	62	75	75	95	95
WEIGHT/KGS	0.4	0.5	0.7	0.9	1.35	1.65

G.C. SUPPLIES UK LTD

TEL:+44 (0) 161-681-8114

FAX:+44 (0) 161-947-0148

DESC	GLOBE VALVE 600PSI	DRAWING #	ETG-GB1		
APPROVED BY.		DATE	09/11/2009		
DRAWER	<i>Y.J. Lee</i>	MATERIAL		MODIFICATION	