



No.	PART NAME	MATERIAL
1	BODY	A351 CF8M
2	END CAP	A351 CF8M
3	BALL	A351 CF8M Gr.CF8M
4	BALL SEAT	RPTFE
5	BODY SEAL	PTFE
6	STEM	A276 TYPE 316
7	THRUST WASHER	RPTFE
8	STEM PACKING	PTFE
9	GLAND NUT	SUS 304
10	STEM WASHER	SUS 304
11	STEM NUT	SUS 304
12	HANDLE	A351-CF8 & S.S. 304
13	HANDLE HEX	SUS 304
14	HANDLE FLANGE	A351-CF8
15	HANDLE SLEEVE	VINYL
16	HANDLE BOLT	SUS 304

SIZE	ϕA	B	C	D	WT/KG
1/4"	11.2	184	57.0	29.5	0.68
3/8"	12.5	184	57.0	29.5	0.65
1/2"	15.0	184	66.1	32.7	0.81
3/4"	20.0	184	75.6	36.6	0.96
1"	25.0	234	87.2	45.2	1.35
1 1/4"	32.0	330	97.0	53.5	2.22
1 1/2"	38.0	330	113.2	59.5	3.18
2"	50.0	330	134.0	71.3	4.38

- * WORKING PRESSURE: 1/4"~2" 2000PSI
- * SPRING RETURN HANDLE
- * FULL PORT: 1/4"~2"
- * TWO PIECE FULL PORT BALL VALVE SCREWED ENDS
- * INVESTMENT CAST BODY
- * FLOATING BALL
- * BLOW-OUT PROOF STEM
- * ADJUSTABLE PACKING GLAND
- * THREADS CONFORM TO ANSI B1.20.1 BS21 DIN259/2999

G.C. SUPPLIES UK LTD

TEL:+44 (0) 161-681-8114

FAX:+44 (0) 161-947-0148

DESC	2PC FULL PORT BALL VALVE SCREWED END 2000PSI	DRAWING #	ETG-SPBV/2K		
APPROVED BY.		DATE	2010/07/14		
DRAWER	<i>Y.J. Lee</i>	MATERIAL		MODIFICATION	